

VISCOM-RI-MARK - SELF WOUND

Issue date : 17/06/2011
Date last modification : 05/08/2011**01287 RI-MARK APP TAPE P200 PAPER****Carrier**

General purpose paper based application tape

Type	Paper
Colour and Finish	White
Weight	80 g/m ² ±10% ISO-536
Thickness	80 μ ±10% ISO 534-80

Adhesive

Medium to high tack rubber based adhesive

Reference	
Type	Rubber based
Min. Appl. Temp.	+ 10 °C
Service Temp.	+ 10 dec C to + 80 deg C
Shear	Very high
Tack	Medium N/inch ²
Final Adhesion	Medium N/inch

Liner

Type	-
Colour and Finish	-
Weight	0 g/m ² ±10% ISO 536
Thickness	0 μ ±10% ISO 534

Applications

Self wound application tape offering clean removability as well as clear tearing without adhesive stringing. Excellent for lifting and transferring graphic, included printed, of all sizes

Printing Methods**Shelf life**

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

